



Jpm 1577

REC'D OCT 21 1987

MATERIAL SAFETY DATA SHEET

97367 (4-85)

MSDS NUMBER ▶

56,210-2

PAGE 1

24 HOUR EMERGENCY ASSISTANCE			GENERAL MSDS ASSISTANCE		
SHELL: 713-473-9461 CHEMTREC: 800-424-9300			SHELL: 713-241-4819		
ACUTE HEALTH * + 1	FIRE 1	REACTIVITY 0	HAZARD RATING ▶ LEAST - 0 SLIGHT - 1 MODERATE - 2 HIGH - 3 EXTREME - 4		
*For acute and chronic health effects refer to the discussion in Section III					

BE SAFE
READ OUR PRODUCT
SAFETY INFORMATION
... AND
PASS IT ON
(PRODUCT LIABILITY LAW
REQUIRES IT)

SECTION I		NAME
PRODUCT ▶	AEROSHELL(R) GREASE 16	
CHEMICAL NAME ▶	LUBRICATING GREASE	
CHEMICAL FAMILY ▶	HYDROCARBON	
SHELL CODE ▶	70016	

SECTION II-A		PRODUCT/INGREDIENT	
NO.	COMPOSITION	CAS NUMBER	PERCENT
P	AEROSHELL GREASE 16	MIXTURE	100
1	SYNTHETIC ESTER	MIXTURE	78.0
2	SOLVENT REFINED; HYDROTREATED PETROLEUM DISTILLATES	64742-57-0	10.0
3	INORGANIC CLAY	1302-78-9	5.0
4	FATTY ACID AMIDES	64754-98-9	3.0
5	OTHER COMPONENTS	MIXTURE	4.0

SECTION II-B		ACUTE TOXICITY DATA	
NO.	ACUTE ORAL LD50	ACUTE DERMAL LD50	ACUTE INHALATION LC50
P	NOT AVAILABLE		

BASED UPON DATA AVAILABLE TO SHELL, COMPONENT 5 IN THIS PRODUCT IS NOT CONSIDERED HAZARDOUS UNDER OSHA HAZARD COMMUNICATION (29 CFR 1910.1200).

SECTION III	HEALTH INFORMATION
THE HEALTH EFFECTS NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).	
EYE CONTACT MAY BE MILDLY IRRITATING TO THE EYES.	
SKIN CONTACT PROLONGED OR REPEATED CONTACT MAY CAUSE VARIOUS SKIN DISORDERS SUCH AS DERMATITIS, FOLLICULITIS OR OIL ACNE. RELEASE DURING HIGH PRESSURE USAGE MAY RESULT IN INJECTION OF OIL INTO THE SKIN CAUSING LOCAL NECROSIS.	
INHALATION NO SPECIFIC INFORMATION IDENTIFIED.	

INGESTION

NO SPECIFIC INFORMATION IDENTIFIED.

SIGNS AND SYMPTOMS

IRRITATION AS NOTED ABOVE. LOCAL NECROSIS IS EVIDENCED BY DELAYED ONSET OF PAIN AND TISSUE DAMAGE A FEW HOURS FOLLOWING INJECTION.

AGGRAVATED MEDICAL CONDITIONS

PREEXISTING SKIN DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

OTHER HEALTH EFFECTS

THIS SPECIFIC PRODUCT HAS NOT BEEN TESTED IN LONG-TERM, CHRONIC EXPOSURE TESTS. LUBRICATING GREASES ARE GENERALLY CONSIDERED TO BE OF A LOW ORDER OF ACUTE TOXICITY TO HUMANS AND EXPERIMENTAL ANIMALS. HOWEVER, THE HANDLING PROCEDURES AND SAFETY PRECAUTIONS IN THIS MSDS SHOULD BE FOLLOWED TO MINIMIZE EMPLOYEE'S EXPOSURE.

SECTION IV**OCCUPATIONAL EXPOSURE LIMITS**

NO.	OSHA PEL/TWA	OSHA PEL/CEILING	ACGIH TLV/TWA	ACGIH TLV/STEL	OTHER
-----	-----------------	---------------------	------------------	-------------------	-------

NO OSHA/PEL OR ACGIH/TLV HAS BEEN ESTABLISHED.

SECTION V**EMERGENCY AND FIRST AID PROCEDURES****EYE CONTACT**

FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.

SKIN CONTACT

REMOVE CONTAMINATED CLOTHING AND WIPE EXCESS OFF. WASH WITH SOAP AND WATER OR A WATERLESS HAND CLEANER FOLLOWED BY SOAP AND WATER. DO NOT REUSE CLOTHING UNTIL THOROUGHLY CLEANED. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IF MATERIAL IS INJECTED UNDER THE SKIN, GET MEDICAL ATTENTION PROMPTLY TO PREVENT SERIOUS DAMAGE; DO NOT WAIT FOR SYMPTOMS TO DEVELOP.

INHALATION

REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION.

INGESTION

DO NOT INDUCE VOMITING. IN GENERAL, NO TREATMENT IS NECESSARY UNLESS LARGE QUANTITIES OF PRODUCT ARE INGESTED. HOWEVER, GET MEDICAL ADVICE.*

NOTE TO PHYSICIAN

*NOTE TO THE PHYSICIAN: IN GENERAL, EMESIS INDUCTION IS UNNECESSARY IN HIGH VISCOSITY, LOW VOLATILITY PRODUCTS, I.E., MOST OILS AND GREASES.

SECTION VI**SUPPLEMENTAL HEALTH INFORMATION**

NONE IDENTIFIED.

SECTION VII**PHYSICAL DATA**BOILING POINT: NOT AVAILABLE
(DEG F)SPECIFIC GRAVITY: NOT AVAILABLE
(H2O=1)VAPOR PRESSURE: NOT AVAILABLE
(MM HG)

PRODUCT NAME: AEROSHELL(R) GREASE 16

MSDS 56,210-2
PAGE 3

MELTING POINT: NOT AVAILABLE
(DEG F)

SOLUBILITY: INSOLUBLE
(IN WATER)

VAPOR DENSITY: NOT AVAILABLE
(AIR=1)

EVAPORATION RATE (N-BUTYL ACETATE = 1): NOT AVAILABLE

APPEARANCE AND ODOR: LIGHT BROWN, SMOOTH, BUTTERY GREASE SLIGHT ODOR.

SECTION VIII

FIRE AND EXPLOSION HAZARDS

FLASH POINT AND METHOD:
500 DEG F COC/SYNTHETIC ESTER

FLAMMABLE LIMITS /% VOLUME IN AIR
LOWER: N/AV UPPER: N/AV

EXTINGUISHING MEDIA

USE WATER FOG, DRY CHEMICAL OR CO2. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS

DO NOT ENTER CONFINED FIRE SPACE WITHOUT PROPER PROTECTIVE EQUIPMENT INCLUDING A NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS SURROUNDING EQUIPMENT AND STRUCTURES WITH WATER.

SECTION IX

REACTIVITY

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS AND MATERIALS TO AVOID:

AVOID HEAT, OPEN FLAME AND CONTACT WITH STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS

THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDENT ON THE COMBUSTION CONDITIONS. A COMPLEX MIXTURE OF AIRBORNE SOLID, LIQUID PARTICULATES AND GASES WILL EVOLVE WHEN THIS MATERIAL UNDERGOES PYROLYSIS OR COMBUSTION. CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED UPON COMBUSTION.

SECTION X

EMPLOYEE PROTECTION

RESPIRATORY PROTECTION

NOT ORDINARILY REQUIRED.

PROTECTIVE CLOTHING

USE OIL RESISTANT GLOVES AND OTHER CLOTHING AS NEEDED TO MINIMIZE SKIN CONTACT.

SECTION XI

ENVIRONMENTAL PROTECTION

SPILL OR LEAK PROCEDURES

SCOOP UP EXCESS GREASE. CLEAN AREA WITH APPROPRIATE CLEANER.

WASTE DISPOSAL

DISPOSE OF IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL REGULATIONS.

ENVIRONMENTAL HAZARDS

EPA - CLEAN WATER ACT (CWA). THIS PRODUCT IS CLASSIFIED AS AN OIL UNDER SECTION 311 OF THE CLEAN WATER ACT. SPILLS ENTERING (A) SURFACE WATERS OR (B) ANY WATERCOURSES OR SEWERS ENTERING/LEAVING TO SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER, 800-424-8802.

SECTION XII

SPECIAL PRECAUTIONS

STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES.

MINIMIZE SKIN CONTACT. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES, INCLUDING SHOES, THAT CANNOT BE DECONTAMINATED.

SECTION XIII

TRANSPORTATION REQUIREMENTS

DEPARTMENT OF TRANSPORTATION CLASSIFICATION: NOT HAZARDOUS BY D.O.T. REGULATIONS

SECTION XIV

OTHER REGULATORY CONTROLS

THE COMPONENTS OF THIS PRODUCT ARE LISTED ON THE EPA/TSCA INVENTORY OF CHEMICAL SUBSTANCES.

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, SHELL MAKES NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. SHELL ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.

DATE PREPARED: SEPTEMBER 13, 1985

BE SAFE

READ OUR PRODUCT
SAFETY INFORMATION ...AND PASS IT ON
(PRODUCT LIABILITY LAW
REQUIRES IT)

JOHN P. SEPESI

SHELL OIL COMPANY
PRODUCT SAFETY AND COMPLIANCE
P. O. BOX 4320
HOUSTON, TX 77210